

UA-KIL60E-W

# Air Purifier with Humidifying Function

Air purifier with 25000 Plasmacluster Ion-Technology, 3 levels filter system, air purity indicator, for rooms up to 50 sqm.



## HIGHLIGHTS

Plasmacluster Ion Technology emitting positive and negative ions, efficient in:

- \* Killing bacteria, viruses, allergens, molds
- \* Removing odours and static electricity
- \* Improving skin moisture

Efficient air purification thanks to 3 levels of filtration and perfect air circulation guaranteed by 20° back outlet of air

Ion shower mode for extra high ion density

PCI spot mode for high effectiveness in remote areas of the room

Humidification performance: 660 ml/h

Tank capacity: 3,6 l

Air flow: 90 - 408 m<sup>3</sup>/h



## Air Purifier Features

<b>Purifier Type</b>	Combination of Plasmacluster Ion Technology - 3 level filter system - humidifier
<b>Purifying Technology</b>	Plasmacluster Ion Technology emitting positive and negative ions: · killing bacteria, viruses, allergens, molds · removing odours and static electricity · improving skin moisture
<b>PCI Function / Ion Function</b>	PCI / 25000
<b>Filter System</b>	3 types: Pre filter, Odour filter, HEPA filter
<b>Available Settings</b>	5: max / med / low / pollen / sleep
<b>Air Flow Angle</b>	20°
<b>Integrated Sensors</b>	PM2.5 (3 digits) / dust sensor, odour sensor, humidity sensor, temperature sensor, light sensor
<b>Applicable Area (Without Humidity Function)</b>	up to 50 sqm
<b>Applicable Area (With Humidity Function)</b>	up to 50 sqm
<b>Air Flow (m³/h)</b>	90 - 408 m³/h
<b>Humidification Performance (ml/h)</b>	230 - 660 ml/h
<b>Tank Capacity (L)</b>	3,6
<b>Noise Level (dB)</b>	20-51
<b>Lifetime Of Filters</b>	10 Years
<b>Air Humidification Function</b>	Yes
<b>Air Quality Indicator</b>	Yes
<b>Filter Change Indicator</b>	Yes
<b>Air Purifier Timer Function</b>	Yes
<b>Air Purifier Child Lock</b>	Yes

## Design

<b>Handles</b>	Integrated
<b>Air Purifier Housing Material</b>	Plastic
<b>Air Purifier Housing Colour</b>	White
<b>Wheels</b>	Yes

## Power Information

<b>Power Requirements</b>	AC 220-240 V ~ 50/60 Hz
<b>Power Consumption</b>	5,5 - 61 W
<b>Standby Power Consumption</b>	1.0
<b>Safety Logo Certification</b>	CE (EMC, LVD, RoHS, ErP), REACh/PAH/SCCP
<b>Plug</b>	CE Plug
<b>Auto Standby Timer</b>	Yes
<b>AC Operated</b>	Yes

## Logistic Information

<b>Net Size (W x H x D in mm)</b>	400 x 686 x 339
<b>Box Size (W x H x D in mm)</b>	485 x 760 x 417
<b>Net Weight (kg)</b>	10,8
<b>Gross Weight (kg)</b>	14
<b>Units on Pallet</b>	4
<b>Packaging Content</b>	Product, Manual, Warranty Card
<b>EAN</b>	4974019190266