

8K LCD display

LV-70X500E

A new standard in image precision



- 70" (177cm) diagonal LCD
- HDR High Dynamic Range
- Media Player for 8K still images and 4K videos
- Native 8K 7680 x 4320 Pixel Resolution
- 10-Bit Extended Colour Range
- Direct LED backlight with local dimming, 216 areas

Specifications

DISPLAY MODULE DATA

Panel Technology	LCD TFT
Native Resolution (Pixels)	7860 x 4320
Diagonal Size (inches / cm)	70 / 177
Aspect Ratio	16:9
Backlight Technology	Direct LED
Brightness (cd/m2)	400 (Peak Brightness 1000 cd / m²)
Contrast Ratio	3000:1 (1.000.000:1)
Display Colours	10-Bit
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) 0 CR >10	176 / 176

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100 - 240 / 50-60
Power Consumption (W) (Operating MAX)	445
Power Consumption (W) (Standby)	0.5
Operating Temperature (oC)	0 - 35
Humidity (%)	20 - 80
Heat Dissipation (BTU/h) MAX	1519

INSTALLATION

Landscape	•
Mounting (VESA/Number of Points/Pitch mm)	400mm X 400mm

CONNECTIVITY (CONTROL/SERIAL DATA)

LAN Port	1
----------	---

KEY SPECIFICATIONS

HDR High Dynamic Range	Auto / HLG / PQ / SDR
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	•
Built in Speakers (W)	2x 10W + 15W Subwoofer
Computer Input - Plug and Play	•
Power Management	•
Cabinet Colour	BLACK
Fanless	•
Fan Control	0
Temperature Sensor	•
Multi Language OSD	•
Screen Adjustment	•
Colour Temperature Adjustment	•
Gamma Adjustment	•
Temperature Control	•

WEIGHTS AND MEASURES

Product Dimensions (W/H/D) mm	1564 / 910 / 92
Product Weight Without Stand (Kg)	42,5

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	8x (HDMI2.0a) for 8K you need 4x HDMI
------	---------------------------------------

ACCESSORIES

Remote Control Transmitter	STD
Operation Manual	via GUI
Power Cord	STD
Battery	STD AA x 2

