

# Sharp MultiSync P656



- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.

# Specifications

## DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Diagonal Size (inches / cm)	64.5 / 163.9
Aspect Ratio	16:9
Brightness (cd/m2)	700
Contrast Ratio	≥ 8000:1
Pixel Pitch (mm H/V)	0.372
Viewing Angle (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	Pro (25)

## POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 V AC; 50 / 60 Hz; internal
Power Consumption (W) (Operating MAX)	160 shipping
Operating Temperature (oC)	+0 to +40
Storage Temperature [°C]	-20 to 60
Humidity (%)	20 to 80
Storage Humidity [%]	10 to 80

## INSTALLATION

Landscape	•
Portrait	•
Horizontal	•
Mounting (VESA/Number of Points/Pitch mm)	4 holes; 400 x 400 (FDMI)

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

HDMI	1
DisplayPort	1

## ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Battery	Yes

## KEY SPECIFICATIONS

Special Characteristics	CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler
24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight; additional services available
Local Dimming	•
Power Management	•
Temperature Sensor	•
Brightness Sensor	•

## WEIGHTS AND MEASURES

Bezel Size (L/R) mm	11
Bezel Size (U/L) mm	11 / 13.9
Product Dimensions (W/H/D) mm	1,454.5 x 832.4 x 59.5
Shipping Carton Dimensions (W/H/D) mm	1,620 x 950 x 185
Product Weight Without Stand (Kg)	26
Shipping Weight (Kg)	35

## CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1

## CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	2
USB	2
Other	USB-C x 2

